

DATASHEET

19" Server Cabinet PRO 24U, 600x800 mm, F+R 2-Part, RAL9005



Bild zeigt: PRO-4288TS.P2
Picture shows: PRO-4288TS.P2





Bild zeigt: PRO-4288TS.P2
Picture shows: PRO-4288TS.P2

General data

The 19" server cabinet PRO 24 U from EFB-Elektronik in 600 x 800 mm and black is designed for the structured installation of active and passive components in demanding network and IT environments. With a fixed frame, baying-compatible design and high mechanical load-bearing capacity, it is suitable for installations with high space and cabling requirements.

- Split perforated steel doors front and rear – Improve air permeability and support efficient expansion in the network and IT environment.
- Passive ventilation and cable entries in the roof and floor – Enable flexible routing without additional active cooling.
- Baying-compatible design with front and rear mounting levels – Facilitates modular construction and simplifies on-the-fly maintenance.

The cabinet is based on a screwed, completely pre-assembled frame and offers 24 U with a maximum load capacity of 1000 kg. The offset profile rails and the mounting levels at the front and rear create additional flexibility in terms of loading. The roof and floor each have two pre-punched, break-out openings. These can be closed again using 19" 2U blind plates. The floor is also equipped with a break-out opening type A. The front and rear doors open up to 270° and are locked with a 1-point quarter-turn latch with swing handle. The door hinges are replaceable. This means that access remains easy to control, even with dense loading.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Server Cabinet PRO 24U, 600x800 mm, F+R 2-Part, RAL9005

Technical details

- Number of doors: 2
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated steel door split
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 1-point quarter-turn latch with swing handle
- Rear door locking: 1-point quarter-turn latch with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties

Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 2 pre-cut, breakable openings (front, back), each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" server cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Server Cabinet PRO 24U, 600x800 mm, F+R 2-Part, RAL9005

Number of cartons	1
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	True
Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 %
Perforation level rear door	> 80 %
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel perforated 2-part
Type of front door	Steel perforated 2-part
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
PRO-2468TS.P2	19" Server Cabinet PRO 24U, 600x800 mm, F+R 2-Part, RAL9005	black	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	1000 kg	24 U	1-point latch locking mechanism with swivel lever	600 mm	False	False	1163 mm	9005	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

