

DATASHEET

19" Network Cabinet PRO-Modular 24U, 800x800 mm, RAL7035









General data

The 19" network cabinet PRO 24 U from EFB-Elektronik in 800 x 800 mm and RAL 7035 is designed for the structured installation of active and passive components in the network and IT environment. The screwed, completely pre-assembled frame provides a stable basis for installation and later expansion.

• Bolted, completely pre-assembled frame with 1000 kg load capacity – Ensures high mechanical stability and reduces assembly effort.
• Passive ventilation, air inlet in the floor and cable entries in the roof and floor – Supports clean ducting without active cooling.
• Baying-compatible design with 24 U and 800 x 800 mm – Allows flexible system expansion with a compact footprint.

For practical removal, passive ventilation, the air inlet in the floor and pre-punched and break-out cable entries in the roof and floor are available. The mounting levels at the front and rear facilitate assembly and the offset profile rails support the structured device structure. This means that the cabinet remains clear and easily adaptable, even with high cabling effort.

Technical details
• Width: 800 mm
• Height: 1163 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO-Modular 24U, 800x800 mm, RAL7035

• Depth: 800 mm
• Number of rack units (U): 24 U
• Category: 19" cabinet frame in accordance with DIN 41494
• Design: with fixed frame
• Design of the profile rail: offset
• Finish of the surface: powder-coated
• Colour: grey
• Degree of protection: IP20 according to EN 60529 for installed doors and side panels
• Type of ventilation: passive
• Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
• Cable entry roof/floor: roof and floor with 4 pre-punched, break-out openings each, circumferential, each 450 x 89 mm, resealable by means of a 19" 2U blank plate
• With earthing: Yes
• With roof panel: Yes
• Mounting level: front and rear
• Reversible front door hinging: Yes
• Reversible rear door hinging: Yes
• Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
• Max. load capacity: 1000 kg
• Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
• Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 4 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" rack frame according to DIN41494
Degree of protection	IP20 according to EN60529 with installed doors and side panels
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO-Modular 24U, 800x800 mm, RAL7035

Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Without
Type of front door	without
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	False
With earthing	True
With front door	False
With roof plate	True
With sidewall	False
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Material front door	Material rear door	Max. load capacity	Number of height units	Width	With vertical cable management	Height	RAL-number	Number of doors
PRO-2488GR.0D	19" Network Cabinet PRO-Modular 24U, 800x800 mm, RAL7035	grey	800 mm	Without	Without	1000 kg	24 U	800 mm	False	1163 mm	7035	-
PRO-4288GR.0D	19" Network Cabinet PRO-Modular 42U, 800x800 mm, RAL7035	grey	800 mm	Without	Without	1000 kg	42 HE	800 mm	False	1963 mm	7035	-
PRO-4288TS.0D	19" Network Cabinet PRO-Modular 42U, 800x800 mm, RAL9005	black	800 mm	Without	Without	1000 kg	42 HE	800 mm	False	1963 mm	9005	-

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO-Modular 24U, 800x800 mm, RAL7035

PRO-4788GR.0D	19" Network Cabinet PRO-Modular 47U, 800x800 mm, RAL7035	grey	800 mm	Without	Without	1000 kg	47 U	800 mm	False	2186 mm	7035	-

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION