DATASHEET

19" Server Cabinet PRO 42U, 1000x1200 mm, F+R=2--part, RAL7035











General data

The 19" server cabinet PRO from EFB-Elektronik in 1000 x 1200 mm and RAL 7035 is designed for demanding installations in the network and IT environment. The bolted, completely pre-assembled frame, the 42 U and the baying-compatible design create a stable basis for the structured installation of active and passive components.

• 1000 x 1200 mm with 42U – Provides generous installation space for extensive assembly and clean separation of components.
• 2-part perforated steel doors front and rear – Aid air circulation and facilitate access to the installed technology.
• Baying compatible PRO construction with a load capacity of up to 1,360 kg – Creates mechanical reserves for dense expansions and later expansions.

The cabinet is designed for high cabling density and changing expansion requirements. Passive ventilation operates without active cooling, while the roof and floor, each with six pre-punched, break-out openings and the air inlet in the floor, allow flexible cable entries. This is complemented by mounting levels at the front and rear, interchangeable door hinges, a door opening angle of 270° at the front and rear doors and a 3-point rod closure with swing handle. The front door is intended for a replaceable profile half-cylinder in accordance with DIN 18252 (30/10 mm), which facilitates integration into existing locking systems.

Technical details

This datasheet was created automatically on 24-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Server Cabinet PRO 42U, 1000x1200 mm, F+R=2--part, RAL7035

- Number of doors: 2
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated steel door split
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 3-point bar closure with swing handle
- Rear door locking: 3-point rod closure with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 6 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" server cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)

This datasheet was created automatically on 24-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Server Cabinet PRO 42U, 1000x1200 mm, F+R=2--part, RAL7035

PHC replaceable rear door	True
Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 %
Perforation level rear door	> 80 %
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel perforated 2-part
Type of front door	Steel perforated 2-part
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
PRO-4202GR.P2	19" Server Cabinet PRO 42U, 1000x1200 mm, F+R=2-part, RAL7035	grey	1200 mm	3-point rod locking mechanism with swivel lever	Steel	Steel	1360 kg	42 HE	3-point rod locking mechanism with swivel lever	1000 mm	False	False	1963 mm	7035	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION