
DATASHEET


19" Network Cabinet PRO 42U, 600x800 mm, RAL7035











General data

The 19" network cabinet PRO 42 U from EFB-Elektronik in 600 x 800 mm and RAL 7035 is designed for the structured installation of active and passive components in the network and IT environment. The design combines high mechanical stability with practical equipment for installations with increased space and cabling requirements.

• 42U and 600 x 800 mm – Offer a lot of installation height in a compact footprint and create reserves for the expansion of network components.
• Front glass door and rear steel door – Allow visual inspection while providing robust protection of the built-in technology.
• Baying compatible, passively ventilated and with cable entries in the roof, floor and rear door – Supports flexible expansion and clean routing without active cooling.

The cabinet is designed as a 19" system in accordance with DIN 41494 and is built with a fixed frame and a screwed, completely pre-assembled frame. The passive ventilation, the IP20 protection class and the maximum load capacity of 1000 kg make the system suitable for demanding IT installations. Mounting levels at the front and rear as well as interchangeable door hinges on the front and rear doors facilitate assembly, maintenance and subsequent adjustments during operation.

Technical details
• Number of doors: 2
• Degree of protection: IP20 according to EN 60529

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO 42U, 600x800 mm, RAL7035

• Type of ventilation: passive
• Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
• With earthing: Yes
• With roof panel: Yes
• With front door: Yes
• With side panels: Yes
• With rear door: Yes
• Mounting level: front and rear
• Front door design: one-piece glass door (certified safety glass, glass thickness 5 mm)
• Front door opening angle: 270°
• Rear door opening angle: 110°
• Front door locking: 3-point bar closure with swing handle
• Rear door locking: 2-point quarter-turn latch
• Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
• Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
• Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry rear door	3U panel including brush, opening 690 x 67 mm, usable from the bottom or top
Cable entry roof/floor	Roof and base each with 2 pre-cut, breakable openings (front, back), each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	110 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
PHC replaceable front door	True, according to DIN18252 (30/10 mm)

DATASHEET

19" Network Cabinet PRO 42U, 600x800 mm, RAL7035

PHC replaceable rear door	False
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Toolless depth adjustment	False
Type of back door	Steel door 1-part
Type of front door	Glass door 1-part (certified safety glass, glass thickness 5 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With vertical cable management	Height	RAL-number	Number of doors
PRO-1868GR.G1SV	19" Network Cabinet PRO 18U, 600x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	18 U	2-point latch locking mechanism	600 mm	False	896 mm	7035	2
PRO-2468GR.G1SV	19" Network Cabinet PRO 24U, 600x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	24 U	2-point latch locking mechanism	600 mm	False	1163 mm	7035	2
PRO-3368GR.G1SV	19" Network Cabinet PRO 33U, 600x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	33 HE	2-point latch locking mechanism	600 mm	False	1563 mm	7035	2
PRO-4268GR.G1SV	19" Network Cabinet PRO 42U, 600x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	42 HE	2-point latch locking mechanism	600 mm	False	1963 mm	7035	2

DATASHEET

19" Network Cabinet PRO 42U, 600x800 mm, RAL7035

PRO-4268TS.G1SV	19" Network Cabinet PRO 42U, 600x800 mm, RAL9005	black	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	42 HE	2-point latch locking mechanism	600 mm	True	False	1963 mm	9005	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION