
DATASHEET


Network Cabinet PRO 42U, 800x1000 mm, RAL9005











General data

The 19" network cabinet PRO from EFB-Elektronik in 800 x 1000 mm and black is designed for demanding network and IT environments. The 42 U version combines high mechanical stability with practical equipment for the structured installation of active and passive components.

• 1360 kg maximum load capacity and bolted frame – Provides high mechanical reserves for dense assembly and later expansion.
• One-piece safety glass front door and steel rear door – Allows visual inspection while providing robust protection of contents.
• Passive ventilation, IP20 and baying-compatible design – Supports thermally non-critical operation and facilitates modular expansion.

The cabinet is designed for installations with a large footprint and extensive cabling. The mounting levels at the front and rear facilitate the positioning of the 19" components. The one-piece glass door with a large opening angle and the rear door support access during maintenance and removal. The cable entries in the roof and floor as well as the brush panel in the rear door ensure clean routing without active cooling.

Technical details
• Number of doors: 2
• Degree of protection: IP20 according to EN 60529
• Type of ventilation: passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet PRO 42U, 800x1000 mm, RAL9005

• Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
• With earthing: Yes
• With roof panel: Yes
• With front door: Yes
• With side panels: Yes
• With rear door: Yes
• Mounting level: front and rear
• Front door design: one-piece glass door (certified safety glass, glass thickness 5 mm)
• Front door opening angle: 270°
• Rear door opening angle: 110°
• Front door locking: 3-point bar closure with swing handle
• Rear door locking: 2-point quarter-turn latch
• Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
• Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
• Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry rear door	3U panel including brush, opening 690 x 67 mm, usable from the bottom or top
Cable entry roof/floor	Roof and base each with 4 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	110 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet PRO 42U, 800x1000 mm, RAL9005

Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel door 1-part
Type of front door	Glass door 1-part (certified safety glass, glass thickness 5 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With vertical cable management	Height	RAL-number	Number of doors
PRO-2480GR.G1SV	19" Network Cabinet PRO 24U, 800x1000 mm, RAL7035	grey	1000 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1360 kg	24 U	2-point latch locking mechanism	800 mm	False	1163 mm	7035	2
PRO-3380GR.G1SV	19" Network Cabinet PRO 33U, 800x1000 mm, RAL7035	grey	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	33 HE	2-point latch locking mechanism	800 mm	False	1563 mm	7035	2
PRO-3380TS.G1SV	19" Network Cabinet PRO 33U, 800x1000 mm, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	33 HE	2-point latch locking mechanism	800 mm	False	1563 mm	9005	2
PRO-4280GR.G1SV	Network Cabinet PRO 42U, 800x1000 mm, RAL7035	grey	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	42 HE	2-point latch locking mechanism	800 mm	False	1963 mm	7035	2
PRO-4280TS.G1SV	Network Cabinet PRO 42U, 800x1000 mm, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	42 HE	2-point latch locking mechanism	800 mm	False	1963 mm	9005	2

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet PRO 42U, 800x1000 mm, RAL9005

PRO-4780GR.G1SV	Network Cabinet PRO 47U, 800x1000 mm, RAL7035	grey	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	47 U	2-point latch locking mechanism	800 mm	False	2186 mm	7035	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION