



DATASHEET

19" Server Cabinet PRO 42U, 800x800 mm, F=1-Part R=2-Part, RAL7035



General data

The 19" PRO network cabinet with 42 U from the EFB-Elektronik brand in 800 x 800 mm and RAL 7035 is designed for the structured installation of network and IT components. It combines a robust frame construction with practical equipment for applications with high space and cabling requirements.

- 42U in 19-inch format – Provides plenty of expansion margin for active and passive components in a compact cabinet depth.
- Perforated Steel Front Door and Perforated Split Rear Door – Improve airflow and facilitate visual inspection of the assembly.
- Pre-assembled fixed frame and baying-compatible design – Reduce assembly effort and make it easier to set up rows of cabinets.

The cabinet is designed for installations where mechanical stability, good accessibility and clean ducting come together. The passive ventilation works without active cooling, while the cable entries in the roof and floor support flexible cable routing. Thanks to mounting levels at the front and rear, interchangeable door hinges and the door opening angles of 270°, the cabinet can be easily equipped and maintained during operation. The load capacity of 1000 kg and the IP20 protection class round off the design for demanding but thermally non-critical environments.

Technical details

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Server Cabinet PRO 42U, 800x800 mm, F=1-Part R=2-Part, RAL7035

- Number of doors: 2
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated one-piece steel door
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 3-point bar closure with swing handle
- Rear door locking: 3-point rod closure with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Width: 800 mm
- Height: 1963 mm
- Depth: 800 mm
- Number of rack units (U): 42 U
- Max. load capacity: 1000 kg
- Colour: grey
- Rear door design: perforated steel door split
- Reversible front door hinging: Yes
- Reversible rear door hinging: Yes
- Design: with fixed frame
- Front door material: steel
- Rear door material: steel
- Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a single-use pallet

Technical properties

Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 4 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" server cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

19" Server Cabinet PRO 42U, 800x800 mm, F=1-Part R=2-Part, RAL7035

Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	True
Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 %
Perforation level rear door	> 80 %
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel perforated 2-part
Type of front door	Steel perforated 1-part
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
--------	-------------	--------	-------	---------------------------	---------------------	--------------------	--------------------	------------------------	--------------------------	-------	------------------	--------------------------------	--------	------------	-----------------

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" Server Cabinet PRO 42U, 800x800 mm, F=1-Part R=2-Part, RAL7035

PRO-2488GR.P1P2	19" Server Cabinet PRO 24U, 800x800 mm, F=1-Part R=2-Part, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	1000 kg	24 U	3-point rod locking mechanism with swivel lever	800 mm	False	False	1163 mm	7035	2
PRO-4288GR.P1P2	19" Server Cabinet PRO 42U, 800x800 mm, F=1-Part R=2-Part, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Steel	Steel	1000 kg	42 HE	3-point rod locking mechanism with swivel lever	800 mm	False	False	1963 mm	7035	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

