
DATASHEET


Network Cabinet PRO 47U, 800x1000 mm, RAL7035











General data

The 19" network cabinet PRO 47 U of the EFB-Elektronik brand in 800 x 1000 mm and RAL 7035 is designed for demanding applications in the network and IT environment. The combination of fixed frame, high mechanical stability and well thought-out equipment supports the structured installation of active and passive components.

• Load capacity up to 1,360 kg – The construction remains stable even when densely populated and offers reserve for later expansion.
• Cable entries in the roof, floor and rear door – cables can be routed cleanly and flexibly without unnecessarily impairing passive air flow.
• 270° front door with replaceable door hinge – Facilitates maintenance, alignment and access to the installed technology during operation.

The completely pre-assembled, screwed version with fixed frame reduces the installation effort and creates a resilient basis for removal during operation. With mounting levels at the front and rear as well as the 19" grid in accordance with DIN 41494, the equipment remains flexible. The passive ventilation, the break-out openings in the roof and floor and the brush panel on the rear door support clean cable routing and thermally non-critical operation.

Technical details
• Number of doors: 2
• Degree of protection: IP20 according to EN 60529
• Type of ventilation: passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet PRO 47U, 800x1000 mm, RAL7035

• Floor air inlet: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
• With earthing: Yes
• With roof panel: Yes
• With front door: Yes
• With side panels: Yes
• With rear door: Yes
• Mounting level: front and rear
• Front door design: one-piece glass door made of certified safety glass, glass thickness 5 mm
• Rear door design: one-piece steel door
• Reversible front door hinging: Yes
• Reversible rear door hinging: Yes
• Front door opening angle: 270°
• Rear door opening angle: 110°
• Front door locking: 3-point bar closure with swing handle
• Locking of the rear door: 2-point quarter-turn latch
• Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
• Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
• Packaging: Delivered in transport packaging on a single-use pallet
• Number of height units: 47 U
• Width: 800 mm
• Height: 2186 mm
• Depth: 1000 mm
• Max. load capacity: 1360 kg
• Baying compatible: Yes

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry rear door	3U panel including brush, opening 690 x 67 mm, usable from the bottom or top
Cable entry roof/floor	Roof and base each with 4 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	110 °

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet PRO 47U, 800x1000 mm, RAL7035

Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	False
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel door 1-part
Type of front door	Glass door 1-part (certified safety glass, glass thickness 5 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With vertical cable management	Height	RAL-number	Number of doors
PRO-2480GR.G1SV	19" Network Cabinet PRO 24U, 800x1000 mm, RAL7035	grey	1000 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1360 kg	24 U	2-point latch locking mechanism	800 mm	False	1163 mm	7035	2
PRO-3380GR.G1SV	19" Network Cabinet PRO 33U, 800x1000 mm, RAL7035	grey	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	33 HE	2-point latch locking mechanism	800 mm	False	1563 mm	7035	2

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Network Cabinet PRO 47U, 800x1000 mm, RAL7035

PRO-3380TS.G1SV	19" Network Cabinet PRO 33U, 800x1000 mm, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	33 HE	2-point latch locking mechanism	800 mm	False	1563 mm	9005	2
PRO-4280GR.G1SV	Network Cabinet PRO 42U, 800x1000 mm, RAL7035	grey	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	42 HE	2-point latch locking mechanism	800 mm	False	1963 mm	7035	2
PRO-4280TS.G1SV	Network Cabinet PRO 42U, 800x1000 mm, RAL9005	black	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	42 HE	2-point latch locking mechanism	800 mm	False	1963 mm	9005	2
PRO-4780GR.G1SV	Network Cabinet PRO 47U, 800x1000 mm, RAL7035	grey	1000 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1360 kg	47 U	2-point latch locking mechanism	800 mm	False	2186 mm	7035	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION