




DATASHEET

19" Network Cabinet PRO-Modular 47U, 800x800 mm, RAL7035



General data

19" rack frame according to DIN41494

Screwed steel sheet frame, completely pre-assembled, self-ventilated, dismountable

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Contrariwise numbering of rack units at the 19" profiles

Delivery without front/rear door and side walls for modular, individual configuration

For installed front and rear door, door stop left or right-sided possible

Cabinets stackable side-by-side with and without removal of the side walls, baying set (Art.-No. PRO-ANR0X), otherwise screwable via screw set M6

Roof and bottom with 4/6 pre-punched openings for cable entry (450 x 90 mm), for 600 mm cabinet width cable entry only rear

Roof prepared for accommodation of 2-fan or 4-fan units, bottom with pre-punched opening for filter or cable entry modules

Internal earthing of all cabinet sections

Pre-assembled earthing bar rear-sided in the middle of the cabinet (ports: 2 x M5 + 2 x 8 mm)

Max. load 1000 kg (depths 600 / 800 mm) resp. 1360 kg (depths 1000 / 1200 mm for >24U)

Paint finish RAL7035, light grey / RAL9005, jet black

Protection degree IP20

Included accessories: 1 x brush, earthing bar pre-installed, 4 x levelling feet M12, 2 x key

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

19" Network Cabinet PRO-Modular 47U, 800x800 mm, RAL7035

Delivery in transport packaging on disposable pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 4 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" rack frame according to DIN41494
Degree of protection	IP20 according to EN60529 with installed doors and side panels
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Frame	screwed together, completely pre-assembled
Material	Stahl
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	pulverbeschichtet
Type of back door	Without
Type of front door	without
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	False
With earthing	True
With front door	False
With roof plate	True
With sidewall	False

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

19" Network Cabinet PRO-Modular 47U, 800x800 mm, RAL7035

With socket | False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Material front door	Material rear door	Max. load capacity	Number of height units	Width	With vertical cable management	Height	RAL-number	Number of doors
PRO-2488GR.0D	19" Network Cabinet PRO-Modular 24U, 800x800 mm, RAL7035	grey	800 mm	Without	Without	1000 kg	24 HE	800 mm	False	1163 mm	7035	-
PRO-4288GR.0D	19" Network Cabinet PRO-Modular 42U, 800x800 mm, RAL7035	grey	800 mm	Without	Without	1000 kg	42 U	800 mm	False	1963 mm	7035	-
PRO-4288TS.0D	19" Network Cabinet PRO-Modular 42U, 800x800 mm, RAL9005	Black	800 mm	Without	Without	1000 kg	42 U	800 mm	False	1963 mm	9005	-
PRO-4788GR.0D	19" Network Cabinet PRO-Modular 47U, 800x800 mm, RAL7035	grey	800 mm	Without	Without	1000 kg	47 U	800 mm	False	2186 mm	7035	-

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.

