

DATASHEET

19" Network Cabinet PRO 47U, 800x800 mm, RAL7035











General data

The 19" network cabinet PRO from EFB-Elektronik in 800 x 800 mm and RAL 7035 is designed for demanding network and IT installations. It combines high mechanical stability with practical equipment for the structured installation of active and passive components. With 47 U, completely pre-assembled frame and powder-coated surface, it is designed for resilient and easily organisable installations.

• Front glass door and rear steel door – visual inspection of hardware while providing robust mechanical protection.
• Passive ventilation with cable entries in the roof, floor and rear door – Clean ducting without active cooling.
• Baying-compatible design with earthing and IP20 – Supports modular construction and safe use in protected indoor areas.

The cabinet is suitable for installations with increased space requirements and high cabling costs. The passive ventilation supports thermally non-critical operation, while the break-out floor entry type A and the cable entries in the roof and rear door enable flexible cable routing. The mounting levels at the front and rear, the interchangeable door hinges and the large door opening angles ensure convenient access to the components even during operation. The load capacity of up to 1000 kg underlines the design for demanding IT and network infrastructures.

Technical details
• Number of doors: 2
• Degree of protection: IP20 according to EN 60529
• Type of ventilation: passive

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO 47U, 800x800 mm, RAL7035

• Air inlet floor: Break-out opening type A (380 x 380 mm), e.g. for filter or cable entry modules
• With earthing: Yes
• With roof panel: Yes
• With front door: Yes
• With side panels: Yes
• With rear door: Yes
• Mounting level: front and rear
• Front door design: one-piece glass door (certified safety glass, glass thickness 5 mm)
• Front door opening angle: 270°
• Rear door opening angle: 110°
• Front door locking: 3-point bar closure with swing handle
• Locking of the rear door: 2-point quarter-turn latch
• Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
• Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
• Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout opening type A (380 x 380 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry rear door	3U panel including brush, opening 690 x 67 mm, usable from the bottom or top
Cable entry roof/floor	Roof and base each with 4 pre-cut, breakable openings, all around, each 450 x 89 mm (re-sealable with a 19" 2U blanking plate)
Category	19" network cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °
Door opening angle rear door	110 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
Number of cartons	1
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO 47U, 800x800 mm, RAL7035

Packaging	Delivery in transport packaging on a disposable pallet
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel door 1-part
Type of front door	Glass door 1-part (certified safety glass, glass thickness 5 mm)
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With glazed door	With vertical cable management	Height	RAL-number	Number of doors
PRO-1888GR.G1SV	19" Network Cabinet PRO 18U, 800x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	18 U	2-point latch locking mechanism	800 mm	True	False	896 mm	7035	2
PRO-2488GR.G1SV	19" Network Cabinet PRO 24U, 800x800 mm, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	24 U	2-point latch locking mechanism	800 mm	True	False	1163 mm	7035	2
PRO-2488TS.G1SV	19" Network Cabinet PRO 24U, 800x800 mm, RAL9005	black	800 mm	1-point latch locking mechanism with swivel lever	Glass	Steel	1000 kg	24 U	2-point latch locking mechanism	800 mm	True	False	1163 mm	9005	2
PRO-3388GR.G1SV	19" Network Cabinet PRO 33U, 800x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	33 HE	2-point latch locking mechanism	800 mm	True	False	1563 mm	7035	2
PRO-4288GR.G1SV	19" Network Cabinet PRO 42U, 800x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	42 HE	2-point latch locking mechanism	800 mm	True	False	1963 mm	7035	2

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Network Cabinet PRO 47U, 800x800 mm, RAL7035

PRO-4788GR.G1SV	19" Network Cabinet PRO 47U, 800x800 mm, RAL7035	grey	800 mm	3-point rod locking mechanism with swivel lever	Glass	Steel	1000 kg	47 U	2-point latch locking mechanism	800 mm	True	False	2186 mm	7035	2

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION