



DATASHEET

Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005



General data

The 19" co-location cabinet PRO of the EFB-Elektronik brand in 800 x 800 mm and RAL 9005 is designed for demanding applications in the network and IT environment. The version with fixed frame and 2 x 20 U combines a resilient construction with a practical interior layout for active and passive components.

- 2 x 20U in 800 x 800 mm – Creates a clearly structured assembly basis for systematic expansion in the co-location environment.
- Perforated steel doors front and rear – support air exchange and combine mechanical protection with a functional door design.
- Stackable PRO design with earthing and IP20 – Facilitates modular expansion and ensures defined indoor use.

The mounting levels at the front and rear, the 270° opening front and rear doors and the 1-point quarter-turn latches

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005

with swing handle on both doors ensure technical depth. The front door can be secured to DIN 18252 via a replaceable profile half-cylinder. The passive ventilation and the break-out openings in the floor support flexible cable routing, while the earthing rail, earthing cable and levelling feet round off the installation. The goods are delivered in transport packaging on a disposable pallet.

Technical details

- Number of doors: 4
- Degree of protection: IP20 according to EN 60529
- Type of ventilation: passive
- Floor air inlet: Break-out openings type A (380 x 380 mm, width 800 mm) or type B (380 x 210 mm, width 600 mm), e.g. for filter or cable entry modules
- With earthing: Yes
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes
- With rear door: Yes
- Mounting level: front and rear
- Front door design: perforated one-piece steel door
- Front door opening angle: 270°
- Rear door opening angle: 270°
- Front door locking: 1-point quarter-turn latch with swing handle
- Rear door locking: 1-point quarter-turn latch with swing handle
- Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
- Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
- Packaging: Delivered in transport packaging on a one-way pallet

Technical properties

Active air conditioning	False
Air inlet floor	Breakout openings type A (380 x 380 mm, width 800 mm) or type B (380 x 210 mm, width 600 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 8 pre-cut, breakable openings (4 left, 4 right), each 87 x 44 mm (re-sealable using a screw-on cover)
Category	19" co-location cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005

Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	True
Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 %
Perforation level rear door	> 80 %
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel perforated 1-part
Type of front door	Steel perforated 1-part
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width cable management	With vertical cable management	Height	RAL-number	Number of doors	Suitable Fans	Number of Boxes
PRO-CL2-4288GR.P1	Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL7035	grey	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	2 x 20 HE	1-point latch locking mechanism with swivel lever	800 mm	True	1963 mm	7035	4	PRO-LFD02BT.x	2

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005

PRO-CL2-4288TS.P1	Co-Location Rack PRO, 2 x 20U, 800x800 mm, F+R 1-Part Perforated, RAL9005	black	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	2 x 20 HE	1-point latch locking mechanism with swivel lever	800 mm	True	1963 mm	9005	4	PRO-LFD02BO.xx 2
PRO-CL4-4288TS.P1	Co-Location Rack PRO, 4 x 9U, 800x800 mm, F+R 1-Part Perforated, RAL9005	black	800 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	4 x 10 HE	1-point latch locking mechanism with swivel lever	800 mm	True	1963 mm	9005	8	PRO-LFD02BO.xx 4

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

