

DATASHEET

Co-Location Rack PRO, 4 x 11U, 600x1000 mm, F+R 1-Part Perforated, RAL7035















General data

The 19" co-location cabinet PRO in 600 x 1000 mm and RAL 7035 is designed for demanding areas of application in the network and IT environment. It combines a screwed, completely pre-assembled fixed frame construction with passive ventilation and practical equipment for the structured installation of active and passive components.

• Perforated steel doors front and rear – Aid in airflow while providing a robust enclosure.
• Cable entries in the roof and floor as well as air inlet in the floor – Enable flexible cable routing with clean integration of the infrastructure.
• Baying-compatible design with earthing and IP20 protection class – Supports modular expansion and defined basic protection in the IT environment.

The cabinet is designed for co-location scenarios with clearly structured equipment. The fixed frame version, the front

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Co-Location Rack PRO, 4 x 11U, 600x1000 mm, F+R 1-Part Perforated, RAL7035

and rear mounting levels and the 270° opening front and rear doors facilitate access during maintenance and removal. The quarter-turn latch with swing handle and the replaceable profile half-cylinder receptacle to DIN 18252 support integrated access control. Thanks to the passive ventilation and the pre-punched, break-out openings in the roof and floor, the cable routing remains adaptable.

Technical details
• Number of doors: 8
• Degree of protection: IP20 according to EN 60529
• Type of ventilation: passive
• Floor air inlet: Type A (380 x 380 mm, width 800 mm) or Type B (380 x 210 mm, width 600 mm), e.g. for filter or cable entry modules
• With earthing: Yes
• With roof panel: Yes
• With front door: Yes
• With side panels: Yes
• With rear door: Yes
• Mounting level: front and rear
• Front door design: perforated one-piece steel door
• Front door opening angle: 270°
• Rear door opening angle: 270°
• Front door locking: 1-point quarter-turn latch with swing handle
• Rear door locking: 1-point quarter-turn latch with swing handle
• Replaceable profile half-cylinder in front door: Yes, in accordance with DIN 18252 (30/10 mm)
• Scope of delivery: 1x cabinet, 1 x brush strip, 1 x cage nut set (pack of 20 pieces), earthing rail and earthing cable, 4 x levelling feet M12, 2 x keys
• Packaging: Delivered in transport packaging on a single-use pallet

Technical properties	
Active air conditioning	False
Air inlet floor	Breakout openings type A (380 x 380 mm, width 800 mm) or type B (380 x 210 mm, width 600 mm), e.g. for filter or cable entry modules
Cabinet Series	PRO
Cable entry roof/floor	Roof and base each with 8 pre-cut, breakable openings (4 left, 4 right), each 87 x 44 mm (re-sealable using a screw-on cover)
Category	19" co-location cabinet according to DIN41494
Degree of protection	IP20 according to EN60529
Demountable	True
Door hinge reversible front door	True
Door hinge reversible rear door	True
Door opening angle front door	270 °

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld
fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50
info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Co-Location Rack PRO, 4 x 11U, 600x1000 mm, F+R 1-Part Perforated, RAL7035

Door opening angle rear door	270 °
Frame	screwed together, completely pre-assembled
Material	Steel
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front and rear
PHC replaceable front door	True, according to DIN18252 (30/10 mm)
PHC replaceable rear door	True
Packaging	Delivery in transport packaging on a disposable pallet
Perforation level front door	> 80 %
Perforation level rear door	> 80 %
Scope of delivery	1x cabinet, 1 x brush strip, 1 x cage nut set (20 pieces per pack), grounding rail and grounding cable, 4 x M12 leveling feet, 2 x keys
Stackable	True
Surface finishing	Powder coating
Type of back door	Steel perforated 1-part
Type of front door	Steel perforated 1-part
Type of profile rail	Crank
Type of ventilation	Passive
With backside door	True
With earthing	True
With front door	True
With roof plate	True
With sidewall	True
With socket	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Front door locking system	Material front door	Material rear door	Max. load capacity	Number of height units	Rear door locking system	Width	With vertical cable management	Height	RAL-number	Number of doors	Suitable Fans	Number of Boxes
PRO-CL2-4760GR.P1	Co-Location Rack PRO, 2 x 23U, 600x1000 mm, F+R 1-Part Perforated, RAL7035	grey	1000 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	2 x 23 HE	1-point latch locking mechanism with swivel lever	600 mm	True	2186 mm	7035	4	PRO-LFD02BT.x	2

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Co-Location Rack PRO, 4 x 11U, 600x1000 mm, F+R 1-Part Perforated, RAL7035

PRO-CL4-4760GR.P1	Co-Location Rack PRO, 4 x 11U, 600x1000 mm, F+R 1-Part Perforated, RAL7035	grey	1000 mm	1-point latch locking mechanism with swivel lever	Steel	Steel	600 kg	4 x 11 HE	1-point latch locking mechanism with swivel lever	600 mm	True	2186 mm	7035	8	PRO-LFD02BT.x	4

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION