

DATASHEET

Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL9005



General data

Fan unit with integrated thermostat for use in roof of cabinets Co Location PRO
 Easy mounting at prepared opening B (210 x 380 mm) hanging at cabinet roof
 Power connector IEC C14, power cable please order separately, e.g. EK504.x
 Housing material steel sheet
 Paint finish RAL7035, light grey / RAL9005, jet black
 Scope of delivery: fan unit incl. thermostat, mounting accessories

Technical properties

Air circulator	False
Built as slide-in ventilator	False
Cabinet Series	EFB-Server
Degree of protection	IP20 (mounted)
EMC-version	False
Mounting method	Screw mounting
Operating voltage at AC 50 Hz	230 – 230 V
Roof ventilator	True
Suitable for 19 inch rack mounting	False
Suitable for wall built-in	False
Voltage type	AC
With filter	False

Available variants

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL9005

ArtNr.	Bezeichnung	Colour	Noise Level	Number of fans	Width	Height	Depth	RAL-number	Rated power	Volume flow, freeblowing	Noise emission
PRO-LFD02BT.GR	Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL7035	grey	48 dB	2	380 mm	45 mm	210 mm	7035	44 W	330 m³/h	48 dB(A)
PRO-LFD02BT.TS	Roof Fan 2-Way, with Thermostat, for Co Location PRO and ESV, RAL9005	black	48 dB	2	380 mm	45 mm	210 mm	9005	44 W	330 m³/h	48 dB(A)

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

