

DATASHEET

Swing Frame for PRO 42U, Cabinet Width 800 mm RAL9005



General data

19" swing frame for mounting in 800 mm wide cabinets PRO

Usable height 40U

Max. mounting depth 440 mm (width 800 mm) resp. 180 mm (width 600 mm) due to asymmetrical construction

With door fixing and locking with 2 x latch

Frame stop left and right possible due to turn around 180°

Opening angle max. 120°

Max. load 150 kg

Material Steel sheet, steel profiles

Paint finish RAL7035, light grey

Technical properties

Cabinet Series	PRO
Material	Steel
Model	Swing frame
Packaging	Cardboard
Scope of delivery	1 x Swing frame, Mounting accessories

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

Swing Frame for PRO 42U, Cabinet Width 800 mm RAL9005

Structure/Use	Usable height 38U, max. opening angle 120°. Max. installation depth of 19" components 440 mm. With door stop and locking mechanism. Can be mounted with left or right hinges.
---------------	---

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Max. Load	Max. load capacity	Suitable for enclosure building height	Suitable for enclosure building width	Width	Height	RAL-number	For Cabinet Width
PRO-SWR428A.GR	Swing Frame for PRO 42U, Cabinet Width 800 mm RAL7035	grey	103 mm	150 kg	150 kg	42 HE	800 mm	800 mm	1863.85 mm	7035	800 mm
PRO-SWR428A.TS	Swing Frame for PRO 42U, Cabinet Width 800 mm RAL9005	Black	103 mm	150 kg	150 kg	42 HE	800 mm	800 mm	1863.85 mm	9005	800 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.

