

DATASHEET

Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL9005



General data

2-part steel door, for 42U cabinets PRO in width 800 mm
 3-point-locking with turning handle and profile half-cylinder acc. to DIN18252 / EN1303 (PHC exchangeable by customer)
 Door opening angle 180°
 Paint finish RAL7035, light grey / RAL9005, jet black
 Delivery pre-assembled incl. all hinges, screws, 2 x key

Technical properties

Cabinet Series	PRO
Degree of protection	IP20
Door opening angle	270 °
For Cabinet Width	800 mm
Material	Steel
Model	Symmetrically divided double wing door
Number of height units (U)	42
Profile half-cylinder exchangeable	True
Scope of delivery	Tür, inkl. Scharnieren, Schrauben, Erdungskabel, 2 x Schlüssel

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL9005

Structure/Use	Stahltür, geteilt, mit Schwenkhebel
Surface finishing	Powder coating
Type of closure	3-point rod locking mechanism with swivel lever
Version as glazed door	True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
PRO-TUR428S2.GR	Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL7035	800 mm	grey	1885 mm	722 mm	7035	False	False
PRO-TUR428S2.TS	Door for PRO 42U, W=800, Steel, 2-Part, TH, RAL9005	800 mm	black	1885 mm	722 mm	9005	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

