

DATASHEET

Door for PRO 42U, W=800, Steel, 1-Part, LL, RAL7035, Rear Door



General data

1-part steel door for 42U cabinets PRO in width 800 mm
 For use as standard rear door, 3U panel for cable entry below the door
 2 x latch locking (T3 / 1333, no profile half-cylinder)
 Door opening angle 110° due to quick fasteners
 Paint finish RAL7035, light grey / RAL9005, jet black
 Delivery pre-assembled incl. all hinges, screws, 2 x key

Technical properties

Cabinet Series	PRO
Degree of protection	IP20
Door opening angle	> 120 °
For Cabinet Width	800 mm
Material	Steel
Model	Stop door
Number of height units (U)	42
Profile half-cylinder exchangeable	False

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Door for PRO 42U, W=800, Steel, 1-Part, LL, RAL7035, Rear Door

Scope of delivery	Tür, inkl. Kabeleinführungspanel, Scharnieren, Befestigungsmaterial, Erdungskabel, 2 x Schlüssel
Structure/Use	Stahltür, einteilig, mit 2 x Vorreiberverschluss
Surface finishing	Powder coating
Type of closure	2-point latch locking mechanism
Version as glazed door	True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	RAL-number	EMC-version	Version as door for disconnecting switch interlocking
PRO-TUR428SV.GR	Door for PRO 42U, W=800, Steel, 1-Part, LL, RAL7035, Rear Door	800 mm	grey	1885 mm	722 mm	7035	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

