DATASHEET

Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 6,0m

General data	
Technical properties	
AWG-size	26
Anti-kink sleeve	put-on
Cable construction	4x2
Cable type	SF/UTP
Category	5E
Colour anti-kink sleeve	grey
Colour outer sheath	grey
Conductor Material	Copper
Locking lever	False
Pin assignment	1:1
Silicone-free	False
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)

Available variants

ArtNr.	Bezeichnung	Length
SOPATD120GR-10.0TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 10,0m	10.0 m
SOPATD120GR-2.5TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 2,5m	2.5 m
SOPATD120GR-25.0TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 25,0m	25.0 m
SOPATD120GR-35.0TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 35,0m	35.0 m
SOPATD120GR-4.0TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 4,0m	4.0 m
SOPATD120GR-40.0TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 40,0m	40.0 m
SOPATD120GR-5.0TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 5,0m	5.0 m
SOPATD120GR-6.0TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 6,0m	6 m
SOPATD120GR-7.5TM11	Patchkabel MegaLine D1-20 SF/U flex 4P,,Hirose TM11, 1:1, Farbe: grau, 7,5m	7.5 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 03-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION