

# DATASHEET

USB-A to USB-C cable set 60W QC 3A 0.5m+1m+2m+3m  
grey gold contacts textile coat



## General data

**USB-A to USB Type-C Charging Cable Set - 60W, Textile Sheath, 1 x 0.5m / 1m / 2m / 3m**

Our **USB charging cable set** offers flexible combinations in **4 different lengths** with high-quality cables supporting **up to 60 watts** charging power. The set is ideal for professional use in sales, office, or warehouse environments.

### Product Features:

- **4 x USB-A to USB Type-C charging cables** for fast, reliable charging
- **Supports** up to **60W** and the Quick Charging Standard **QC**
- **480 Mbit/s** data transfer rate
- **Included in the set:** 1 x 0.5 m, 1 x 1 m, 1 x 2 m, 1 x 3 m
- **Gold-plated USB-A and USB Type-C connectors** with **aluminum housing** - for stable connection and long durability

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

# DATASHEET

## USB-A to USB-C cable set 60W QC 3A 0.5m+1m+2m+3m grey gold contacts textile coat

- **Robust textile sheath (space gray)** – abrasion-resistant, kink-resistant, durable
- **Charging lightning bolt icon** as a visual usage aid (no LED)
- **Plastic-free individual packaging**, ready for shipping
- **Environmentally friendly:** paper cable ties, no plastic accessories
- **Application & Target Groups:**

Ideal for system integration, device accessories, workplace cabling, conference technology, and educational or governmental technology. Suitable for notebooks, tablets, smartphones, and all USB-C compatible devices.

| Technical properties                |             |
|-------------------------------------|-------------|
| 3D                                  | False       |
| ARC                                 | False       |
| Backwards compatible                | True        |
| Bending radius (dynamic/static)     | 40 mm       |
| CEC                                 | False       |
| Cable set                           | True        |
| Cable type (passive/active/optical) | passive     |
| Chip                                | False       |
| Connection type connection 1        | Plug        |
| Connection type connection 2        | Plug        |
| Connector 1 angulation              | 180°        |
| Connector 2 angulation              | 180°        |
| Contact Plating                     | gold-plated |
| DSC                                 | False       |
| Dust cover                          | false       |
| Fast Charging technologie           | QC 2.0      |
| HDMI Power                          | False       |
| HDMI certified                      | False       |
| HEC (Ethernet channel)              | False       |
| Halogenfree                         | No          |
| Kink protection                     | True        |
| MSA                                 | False       |
| MST                                 | False       |
| Material Connector Housing          | Aluminium   |
| Material Inner Conductor            | BC          |

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



# DATASHEET

## USB-A to USB-C cable set 60W QC 3A 0.5m+1m+2m+3m grey gold contacts textile coat

|                                |                      |
|--------------------------------|----------------------|
| Material jacket                | PVC+Textile          |
| Max. mating cycles             | 10000                |
| Model                          | Round Cable          |
| Number of poles connection 1   | 4                    |
| Number of poles connection 2   | 5                    |
| Number of shieldings           | double               |
| Operating temperature          | -5 - 45 °C           |
| PCIe Data transfer             | False                |
| Plug dimensions Side 1         | 12 x 4.5 x 20.5mm    |
| Plug dimensions Side 2         | 8.25 x 2.35 x 14.5mm |
| Power Delivery                 | 60 W                 |
| Scope of delivery              | 4xUSB Cable          |
| Shielded                       | True                 |
| Speed                          | 480 Mbit/s           |
| Temperature                    | -20 - 70 °C          |
| Tensile strength (short/long)  | 98,1 N               |
| Type of connector connection 1 | USB-A                |
| Type of connector connection 2 | USB Type-C           |
| Type of packaging              | paper box            |
| VESA certified                 | False                |
| VRR                            | False                |
| Various lengths cable set      | 1x(0.5m+1m+2m+3m)    |
| Version                        | USB 2.0 High-Speed   |
| Warranty                       | 36 months            |
| With termination resistor      | False                |
| eARC                           | False                |

### Available variants

| ArtNr.       | Bezeichnung                                                                      | Colour     | Diameter AWG |
|--------------|----------------------------------------------------------------------------------|------------|--------------|
| USB-AC-00005 | USB-A to USB-C cable set 60W QC 3A 0.5m+1m+2m+3m grey gold contacts textile coat | space grey | 4.0 mm 22AWG |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

