

DATASHEET

Ethernet over VDSL2-Converter (Annex B)



General data

Supports a VDSL connection up to 2km over single pair copper wire
 Provides 100Mbps up and downstream up to 300m
 Features selectable Fast and Interleaved modes
 Selectable fixed data rate and fixed SNR margin
 Features 4 DIP Switches for Configuration Settings
 Low-Latency for Video/Voice/Data applications
 2 x RJ45 LAN Ports, 1 x RJ11 phone, 1 x RJ11 VDSL
 Annex B

Technical properties

Construction type	Single device
Depth	90.0 mm
Ethernet	True
Fast Ethernet	True
Height	28.0 mm
Manufacturer	LevelOne
Number of ports 10/100 Mbps RJ45	1
Type	Annex B

This datasheet was created automatically on 12-10-2026 . Technical changes reserved.



DATASHEET

Ethernet over VDSL2-Converter (Annex B)

Width	120.0 mm
-------	----------

Available variants

ArtNr.	Bezeichnung	Unique
VDS-1202	Ethernet over VDSL2-Converter (Annex B)	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-10-2026 . Technical changes reserved.

