DATASHEET

Inno core centering splicer View8X incl. Inno V12 breaking tool













General data

The View8X from INNO Instrument is a first-class core alignment splicer. The X stands for “eXceed eXpectations”—and that’s exactly what the View8X does: it exceeds your expectations. The South Korean high-end manufacturer’s flagship sets the bench□mark for splicing efficiency. Period.

This device’s features are not lacking in superlatives: Splicing time: 4 seconds. Heating time: 9 seconds. Battery power: 500 work cycles. Magnification: 520 ×. Plus a high-resolution 5-inch color LCD touchscreen, intuitive user interface, robust design, large memory for measured values and docu□mentation images. The View8X is not to be overlooked.

Technical properties

Battery Capacity	9000 mAh

This datasheet was created automatically on 21-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Inno core centering splicer View8X incl. Inno V12 breaking tool

Configuration	Shrink oven
Connections	USB Typ C
Displaysize	5,0"
Electrode Life	6000 arcs
Fiber Count	Single
Heating Time (oven)	9 sec
Magnification	520x
Operating Conditions	Altitude: 0-5000m
Results Storage	10000
Size (WxHxD)	143 x 158 x 162 mm
Splice Mode	128
Splicing Time	4 sec
Storage Conditions	Temperatur: -40 - 80°C
Tension Test	1,96 - 2,25 N
Typical Return Loss	>60 dB
Weight	2.68 KG

Available variants

ArtNr.	Bezeichnung	Model
VIEW-8X	Inno core centering splicer View8X incl. Inno V12 breaking tool	Fusion splice

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION