

DATASHEET

Splice box sliding version 1U without front panel, unequipped, black



General data

Material sheet steel
 With sleeve nut (Art.-No. 80555.1) max. 4 splice cassettes installable
 Cable entry at the rear, prepared for PG16/M20
 Changeable cable entry for straight and angled
 Cable entry in the middle for thinner cable

Technical properties

Depth	244.0 mm
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	sliding version
Suitable for number of module inserts	-
Width	483.0 mm
With front plate	False

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

DATASHEET

Splice box sliding version 1U without front panel, unequipped, black

With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour RAL-number	
VSB-A-GR	Splice box sliding version 1U without front panel, unequipped, grey	grey	7035
VSB-A-SW	Splice box sliding version 1U without front panel, unequipped, black	black	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

