DATASHEET

2U extendable splice box without front panel, unassembled, black







General data

Material sheet steel
With sleeve nut (item no. 80555.1) max. 8 splice cassettes can be installed
Cable entry at the rear, prepared for PG16/M20
Replaceable bracket for straight cable entry
Cable entry in the centre for thinner cables

Technical properties

Mounting method	482.6 mm (19 inch) mounting
Number of height units	2 U
Sliding	sliding
With front plate	False
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	RAL-number
VSB2HE-A-GR	2U extendable splice box without front panel, unassembled, grey	grey	7035

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

2U extendable splice box without front panel, unassembled, black

VSB2HE-A-SW	2U extendable splice box without front panel, unassembled, black	black	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION