DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 750Mbit/s, Dual-Band







General data
Share your wireless network up to 750 Mbit/s
Compatible to the IEEE-802.11ac/a/b/g/n standards
Supports a high level of security using WEP, WPA and WPA2 with IEEE-802.1X
Supports up to 8 SSIDs in connection with WAC-2000/WAC-2003 for a better security in your network
IEEE-802.3af PoE compatible for a easy installation
Ceiling- or wall-mounted models

Technical properties	
Depth	38.5 mm
Frequency band	2.4 GHz and 5 GHz
Height	189 mm
Managed	True
Max. data transmission rate	750 Mbps
Power over Ethernet	True
Width	189 mm

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 750Mbit/s, Dual-Band

Available variants		
ArtNr.	**Bezeichnung**	**Unique**
WAP-8121	Managed PoE WLAN-Ceiling/Wall-Access-Point, 750Mbit/s, Dual-Band	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION