

DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 750Mbit/s, Dual-Band



General data

Share your wireless network up to 750 Mbit/s
 Compatible to the IEEE-802.11ac/a/b/g/n standards
 Supports a high level of security using WEP, WPA and WPA2 with IEEE-802.1X
 Supports up to 8 SSIDs in connection with WAC-2000/WAC-2003 for a better security in your network
 IEEE-802.3af PoE compatible for a easy installation
 Ceiling- or wall-mounted models

Technical properties

Depth	38.5 mm
Frequency band	2.4 GHz and 5 GHz
Height	189 mm
Managed	True
Max. data transmission rate	750 Mbps
Power over Ethernet	True
Width	189 mm

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 750Mbit/s, Dual-Band

Available variants

ArtNr.	Bezeichnung	Unique
WAP-8121	Managed PoE WLAN-Ceiling/Wall-Access-Point, 750Mbit/s, Dual-Band	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

