DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 1200Mbit/s, Dual-Band, MU-MIMO








General data

Share your wireless network up to 1200 Mbit/s
Compatible to the IEEE-802.11a/b/g/n and ac Wave 2 MU-MIMO standards
The MU-MIMO (Multi-User Multiple-Input Multiple-Output) technology allows multiple devices to receive Wi-Fi signal simultaneously. This increases the speed of you entire network.
Supports a high level of security using WEP, WPA and WPA2 with IEEE-802.1X
Supports up to 8 SSIDs in connection with Wireless Lan Controller WAC-2000/WAC-2003 for a better security in your network
IEEE-802.3af PoE compatible for a easy installation
Ceiling- or wall-mounted models

Technical properties

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 1200Mbit/s, Dual-Band, MU-MIMO

Depth	28 mm
Frequency band	2.4 GHz and 5 GHz
Height	198 mm
Managed	True
Max. data transmission rate	1200 Mbps
Number of ports 10/100/1000 Mbps LAN	1
Power over Ethernet	True
Width	198 mm

Available variants

ArtNr.	Bezeichnung	Unique
WAP-8123	Managed PoE WLAN-Ceiling/Wall-Access-Point, 1200Mbit/s, Dual-Band, MU-MIMO	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION