

DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 1200Mbit/s, Dual-Band, MU-MIMO



General data

Share your wireless network up to 1200 Mbit/s

Compatible to the IEEE-802.11a/b/g/n and ac Wave 2 MU-MIMO standards

The MU-MIMO (Multi-User Multiple-Input Multiple-Output) technology allows multiple devices to receive Wi-Fi signal simultaneously. This increases the speed of your entire network.

Supports a high level of security using WEP, WPA and WPA2 with IEEE-802.1X

Supports up to 8 SSIDs in connection with Wireless Lan Controller WAC-2000/WAC-2003 for a better security in your network

IEEE-802.3af PoE compatible for a easy installation

Ceiling- or wall-mounted models

Technical properties

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

Managed PoE WLAN-Ceiling/Wall-Access-Point, 1200Mbit/s, Dual-Band, MU-MIMO

Depth	28 mm
Frequency band	2.4 GHz and 5 GHz
Height	198 mm
Managed	True
Max. data transmission rate	1200 Mbps
Number of ports 10/100/1000 Mbps LAN	1
Power over Ethernet	True
Width	198 mm

Available variants

ArtNr.	Bezeichnung	Unique
WAP-8123	Managed PoE WLAN-Ceiling/Wall-Access-Point, 1200Mbit/s, Dual-Band, MU-MIMO	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

