

DATASHEET

10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035



General data

Steel sheet housing, self-ventilated, screwed, pre-assembled
 Front door lockable, with latch, door opening angle 120°
 Front door fully made of certified safety glass (4 mm)
 Door stop left-sided
 Roof and bottom with cable entry 145 x 70 mm
 Inside 2 x 10" profile rails, depth adjustable in 60 mm raster
 Max. mounting depth 230 mm (at delivery: ca. 170 mm)
 Paint finish RAL7035, light grey / RAL9005, jet black / RAL9010, pure white
 Width 312 mm, height 300 mm
 Max. load 30 kg, protection degree IP20
 Delivery incl. 1 x brush, 1 x plastic cover, key

Technical properties

Cabinet Series	10" Wall Housing BASIC, pre-assembled
Cable entry roof/floor	Roof + Baase, each 145 x 70 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes, by rotating the case 180°

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.



DATASHEET

10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035

Door opening angle front door	120 °
Frame	screwed together, pre-assembled, disassemblable
Installation depth min. - max.	68 - 248 mm
Material	Steel
Model	With permanent frame
Modular spacing	254 mm (10 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	1 cardboard box with carrying handle
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys
Structure/Use	Self-ventilated sheet steel housing, screwed together, pre-assembled.
Surface finishing	powder coating
Type of front door	Full glass door made of certified safety glass (4 mm), lockable, smoke-colored
Type of profile rail	L-shape
Type of ventilation	Passive
With earthing	False
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
WGB-1004GR.30	10" 4U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035	grey	300 mm	215 mm	30 kg	4 U	312 mm	7035
WGB-1004TS.30	10" 4U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005	schwarz	300 mm	215 mm	30 kg	4 U	312 mm	9005
WGB-1004WS.30	10" 4U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9010	weiß	300 mm	215 mm	30 kg	4 U	312 mm	9010

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.



DATASHEET

10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035

WGB-1006GR.30	10" 6U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035	grey	300 mm	304 mm	30 kg	6 U	312 mm	7035
WGB-1006TS.30	10" 6U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005	schwarz	300 mm	304 mm	30 kg	6 U	312 mm	9005
WGB-1006WS.30	10" 6U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9010	weiß	300 mm	304 mm	30 kg	6 U	312 mm	9010
WGB-1009GR.30	10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL7035	grey	300 mm	437 mm	30 kg	9 HE	312 mm	7035
WGB-1009TS.30	10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9005	schwarz	300 mm	437 mm	30 kg	9 HE	312 mm	9005
WGB-1009WS.30	10" 9U Wall Housing, Depth 300 mm, 1-piece, pre-assembled, RAL9010	weiß	300 mm	437 mm	30 kg	9 HE	312 mm	9010

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.

