

DATASHEET

19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035



General data

The 19" wall enclosure BASIC with a depth of 600 mm in RAL 7035 is designed as a robust solution for structured network and IT installations. The unassembled flat-pack design facilitates transport and storage, while the bolted sheet steel construction forms a stable basis for removal.

- Flat-pack design with bolted sheet steel housing – Facilitates transport and storage and reduces the installation effort until commissioning.
- 9U in 19-inch version at 600 mm depth – Creates a clearly defined installation space for network and IT components.
- Full glass door made of certified safety glass with replaceable door hinge – Enables visual inspection and adapts flexibly to the installation situation.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and IP20 protection. The installation depth of 63 to 552 mm, the maximum distance between the 19" levels of 489 mm and the cable entries over the roof and floor support a clean integration of the components. The powder-coated surface, the version in grey RAL 7035 and the load capacity of 80 kg are designed for use in controlled indoor areas.

Technical details

- Number of doors: 1
- Degree of protection: IP20

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035

- Type of ventilation: passive
- Air inlet floor: roof + floor, each 145 x 70 mm
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, not openable
- Mounting level: front
- Front door version: full glass door made of certified safety glass (4 mm), lockable, smoke-coloured
- Front door opening angle: 120°
- Front door locking: lockable
- Scope of delivery: 1x cabinet, 1x brush strip, 1x plastic cover, mounting material, 2x keys
- Packaging: 1 box with carrying handle
- Width: 535 mm
- Height: 437 mm
- Depth: 600 mm
- Installation depth min. - max.: 63 - 552 mm
- Colour: grey
- RAL number: 7035
- Load capacity: 80 kg
- Material: Steel
- Finish of the surface: powder-coated
- Max. distance of the 19" planes: 489 mm

Technical properties

Cabinet Series	19" Wall Housing BASIC, un-assembled
Cable entry roof/floor	Roof + Baase, each 145 x 70 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes, by rotating the case 180°
Door opening angle front door	120 °
Frame	screwed together, unassembled
Installation depth min. - max.	63 - 552 mm
Material	Steel
Max. spacing of the 19" levels	489 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	1 cardboard box with carrying handle

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035

Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys
Structure/Use	19" wall-mounted enclosure, one-piece, type Flat Pack. Screw-on sheet steel enclosure, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Full glass door made of certified safety glass (4 mm), lockable, smoke-colored
Type of profile rail	L-shaped
Type of ventilation	Passive
With earthing	False
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
WGB-1906GR.60	19" 06U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	304 mm	80 kg	6 U	535 mm	7035
WGB-1909GR.60	19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	437 mm	80 kg	9 U	535 mm	7035
WGB-1912GR.60	19" 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	571 mm	80 kg	12 U	535 mm	7035
WGB-1915GR.60	19" 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	707 mm	80 kg	15 U	535 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

