

DATASHEET

19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010



General data

The 19" wall enclosure BASIC in 9 U and 600 mm depth is designed as an unassembled flat-pack solution for demanding interior areas. The bolted sheet steel construction in white according to RAL 9010 forms a stable basis for the 19-inch installation and supports space-saving provision up to installation.

- 9U on 19-inch pitch at 600 mm depth – Creates a well-defined installation space for network and IT components with compact enclosure dimensions.
- Flat-pack design with bolted sheet steel housing – Facilitates transport and storage and reduces assembly effort on the construction site.
- Full glass door made of certified safety glass with replaceable door hinge – Enables visual inspection and adapts flexibly to the installation situation.

In terms of technical design, the housing combines a mounting level at the front with passive ventilation and an IP20 protection class. The cable entry over the roof and floor, each measuring 145 x 70 mm, supports clean integration of the cables. In addition, the powder-coated surface, the installation depth of 63 to 552 mm and the maximum distance between the 19" levels of 489 mm ensure a technically clearly defined installation situation.

Technical details

- Number of doors: 1

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010

- Degree of protection: IP20
- Type of ventilation: passive
- Air inlet floor: cable entry floor, 145 x 70 mm
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, not openable
- Mounting level: front
- Front door version: full glass door made of certified safety glass (4 mm), lockable, smoke-coloured
- Front door opening angle: 120°
- Front door locking: lockable
- Scope of delivery: 1x cabinet, 1x brush strip, 1x plastic cover, mounting material, 2x keys
- Packaging: 1 box with carrying handle

Technical properties	
Cabinet Series	19" Wall Housing BASIC, un-assembled
Cable entry roof/floor	Roof + Baase, each 145 x 70 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes, by rotating the case 180°
Door opening angle front door	120 °
Frame	screwed together, unassembled
Installation depth min. - max.	63 - 552 mm
Material	Steel
Max. spacing of the 19" levels	489 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	1 cardboard box with carrying handle
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys
Structure/Use	19" wall-mounted enclosure, one-piece, type Flat Pack. Screw-on sheet steel enclosure, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Full glass door made of certified safety glass (4 mm), lockable, smoke-colored
Type of profile rail	L-shaped

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010

Type of ventilation	Passive
With earthing	False
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
WGB-1906WS.60	19" 06U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	white	600 mm	304 mm	80 kg	6 U	535 mm	9010
WGB-1909WS.60	19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	white	600 mm	437 mm	80 kg	9 U	535 mm	9010
WGB-1912WS.60	19" 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	white	600 mm	571 mm	80 kg	12 U	535 mm	9010
WGB-1915WS.60	19" 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9010	white	600 mm	707 mm	80 kg	15 U	535 mm	9010

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

