

DATASHEET

19" 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035



General data

19" Wall housing 1-part, type Flat Pack
 Steel sheet housing screwable, not pre-assembled
 Front door fully made of certified safety glass, thickness 4 mm, smoked, tempered, smoothed, antistatic
 Front door lockable, Door opening angle 120°
 Door stop easy changeable (right/left)
 Sidewalls not detachable
 Roof prepared for mounting of 2 x single fans
 Roof and bottom with cable entry 145 x 70 mm
 Inside 2 x 19" profile rails, depth-adjustable, with lateral opening for cable routing
 Paint finish RAL7035 light grey / RAL9005 (jet black) / RAL9010 (pure white)
 Width 535 mm, depth 450 / 600 mm
 Max. load 80 kg (static, equally distributed)
 Protection degree IP20
 Incl. key
 Delivery unassembled in 1 carton with handle

Technical properties

Cabinet Series	19" Wall Housing BASIC, un-assembled
Cable entry roof/floor	Roof + Base, each 145 x 70 mm

This datasheet was created automatically on 12-10-2026 . Technical changes reserved.



DATASHEET

19" 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035

Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes, by rotating the case 180°
Door opening angle front door	120 °
Frame	screwed together, unassembled
Installation depth min. - max.	63 - 552 mm
Material	Steel
Max. spacing of the 19" levels	489 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	1 cardboard box with carrying handle
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys
Structure/Use	19" wall-mounted enclosure, one-piece, type Flat Pack. Screw-on sheet steel enclosure, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Full glass door made of certified safety glass (4 mm), lockable, smoke-colored
Type of profile rail	L-shape
Type of ventilation	Passive
With earthing	False
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
WGB-1906GR.60	19" 06U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	304 mm	80 kg	6 U	535 mm	7035

This datasheet was created automatically on 12-10-2026 . Technical changes reserved.



DATASHEET

19" 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035

WGB-1909GR.60	19" 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	437 mm	80 kg	9 HE	535 mm	7035
WGB-1912GR.60	19" 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	571 mm	80 kg	12 U	535 mm	7035
WGB-1915GR.60	19" 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	707 mm	80 kg	15 U	535 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-10-2026 . Technical changes reserved.

