# DATASHEET

## 19“ 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9005

### General data

19" Wall housing 1-part, type Flat Pack
Steel sheet housing screwable, not pre-assembled
Front door fully made of certified safety glass, thickness 4 mm, smoked, tempered, smoothed, antistatic
Front door lockable, Door opening angle 120°
Door stop easy changeable (right/left)
Sidewalls not detachable
Roof prepared for mounting of 2 x single fans
Roof and bottom with cable entry 145 x 70 mm
Inside 2 x 19" profile rails, depth-dajustable, with lateral opening for cable routing
Paint finish RAL7035 light grey / RAL9005 (jet black) / RAL9010 (pure white)
Width 535 mm, depth 450 / 600 mm
Max. load 80 kg (static, equally distributed)
Protection degree IP20
Incl. key
Delivery unassembled in 1 carton with handle

### Technical properties

| | |
|---|---|
| Cabinet Series | 19" Wall Housing BASIC, un-assembled |
| Cable entry roof/floor | Roof + Baase, each 145 x 70 mm |

**This datasheet was created automatically on 17-10-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## 19“ 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9005

| | |
|---|---|
| Degree of protection | IP20 |
| Demountable | True |
| Door hinge reversible front door | Yes, by rotating the case 180° |
| Door opening angle front door | 120 ° |
| Frame | screwed together, unassembled |
| Installation depth min. - max. | 63 - 552 mm |
| Material | Steel |
| Max. spacing of the 19" levels | 489 mm |
| Model | With permanent frame |
| Modular spacing | 482,6 mm (19 inch) |
| Mounting level | Front side |
| Number of cartons | 1 |
| Number of doors | 1 |
| PHC replaceable front door | No |
| Packaging | 1 cardboard box with carrying handle |
| Scope of delivery | 1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys |
| Structure/Use | 19" wall-mounted enclosure, one-piece, type Flat Pack. Screw-on sheet steel enclosure, not pre-assembled. |
| Surface finishing | Powder coating |
| Type of front door | Full glass door made of certified safety glass (4 mm), lockable, smoke-colored |
| Type of profile rail | L-shape |
| Type of ventilation | Passive |
| With earthing | False |
| With front door | True |
| With roof plate | True |
| With sidewall | Yes, not openable |

### Available variants

| ArtNr. | Bezeichnung | Colour | Depth | Height | Max. Load | Number of height units | Width | RAL-number |
|---|---|---|---|---|---|---|---|---|
| WGB-1906TS.60 | 19“ 06U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9005 | Black | 600 mm | 304 mm | 80 kg | 6 U | 535 mm | 9005 |

**This datasheet was created automatically on 17-10-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## 19“ 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9005

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| WGB-1909TS.60 | 19“ 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9005 | Black | 600 mm | 437 mm | 80 kg | 9 HE | 535 mm | 9005 |
| WGB-1912TS.60 | 19“ 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9005 | Black | 600 mm | 571 mm | 80 kg | 12 U | 535 mm | 9005 |
| WGB-1915TS.60 | 19“ 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL9005 | Black | 600 mm | 707 mm | 80 kg | 15 U | 535 mm | 9005 |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 17-10-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION