DATASHEET

19“ 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035









General data

The 19" wall enclosure BASIC in 600 mm depth and RAL 7035 is designed as a robust solution for demanding installations. The unassembled flat-pack design facilitates transport and storage. The bolted sheet steel construction with fixed frame provides a stable basis for 19-inch installation.

• 15U 19-inch version with 600 mm depth – Creates a clearly defined installation situation for network and IT components.
• Unassembled flat-pack design with bolted sheet steel construction and fixed frame – Facilitates transport and storage and provides a stable base for assembly.
• Full glass door made of certified safety glass, 4 mm, with replaceable door hinge – Allows visual inspection and flexible adaptation to the installation situation.

In terms of technical design, the housing combines a front mounting level with passive ventilation and an IP20 degree of protection. The powder-coated surface and dimensions of 707 mm high, 535 mm wide and 600 mm deep are designed for controlled indoor areas. Cable entries over the roof and floor, each measuring 145 x 70 mm, as well as the maximum distance between the 19" levels of 489 mm, support clean integration of the components.

Technical details
• Number of doors: 1

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19“ 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035

- Degree of protection: IP20
- Type of ventilation: passive
- Air inlet floor: roof and floor, each 145 x 70 mm
- With roof panel: Yes
- With front door: Yes
- With side panels: Yes, not openable
- Mounting level: front
- Front door design: Full glass door made of certified safety glass, 4 mm, lockable, smoke-coloured
- Front door opening angle: 120°
- Front door locking: lockable
- Scope of delivery: 1x cabinet, 1x brush strip, 1x plastic cover, mounting material, 2x keys
- Packaging: 1 box with carrying handle

Technical properties	
Cabinet Series	19" Wall Housing BASIC, un-assembled
Cable entry roof/floor	Roof + Baase, each 145 x 70 mm
Degree of protection	IP20
Demountable	True
Door hinge reversible front door	Yes, by rotating the case 180°
Door opening angle front door	120 °
Frame	screwed together, unassembled
Installation depth min. - max.	63 - 552 mm
Material	Steel
Max. spacing of the 19" levels	489 mm
Model	With permanent frame
Modular spacing	482,6 mm (19 inch)
Mounting level	Front side
Number of cartons	1
Number of doors	1
PHC replaceable front door	No
Packaging	1 cardboard box with carrying handle
Scope of delivery	1x Cabinet, 1x brush strip, 1x plastic cover, Mounting accessories, 2x keys
Structure/Use	19" wall-mounted enclosure, one-piece, type Flat Pack. Screw-on sheet steel enclosure, not pre-assembled.
Surface finishing	Powder coating
Type of front door	Full glass door made of certified safety glass (4 mm), lockable, smoke-colored
Type of profile rail	L-shaped

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19“ 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035

Type of ventilation	Passive
With earthing	False
With front door	True
With roof plate	True
With sidewall	Yes, not openable

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
WGB-1906GR.60	19“ 06U Wall Housing Basic, Depth 600 mm,1-Part, Flat Pack, RAL7035	grey	600 mm	304 mm	80 kg	6 U	535 mm	7035
WGB-1909GR.60	19“ 09U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	437 mm	80 kg	9 U	535 mm	7035
WGB-1912GR.60	19“ 12U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	571 mm	80 kg	12 U	535 mm	7035
WGB-1915GR.60	19“ 15U Wall Housing Basic, Depth 600 mm, 1-Part, Flat Pack, RAL7035	grey	600 mm	707 mm	80 kg	15 U	535 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION