

DATASHEET

Front Door for Wall Housing BASIC 12U



General data

Front door as spare part for wall housing BASIC
Material certified safety glass, thickness 4 mm
Delivery incl. hinges and lock

Technical properties

Cabinet Series	Wall Housings Basic
Degree of protection	IP20
Door opening angle	ca. 120 °
For Cabinet Width	535 mm
Material	Glass
Model	Stop door
Number of height units (U)	6
Profile half-cylinder exchangeable	True
Scope of delivery	inkl. Scharnieren, Schloss, Befestigungsmaterial, 2 x Schlüssel
Structure/Use	Glastür, einteilig, mit Vorreiberverschluss
Surface finishing	Other
Type of closure	Single-point latch locking

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.



DATASHEET

Front Door for Wall Housing BASIC 12U

Version as glazed door

True

Available variants

ArtNr.	Bezeichnung	Building width for cabinet build in	Colour	Height	Width	EMC-version	Version as door for disconnecting switch interlocking
WGB-TUR06	Front Door for Wall Housing BASIC 06U	535 mm	rauchfarben	256 mm	507 mm	False	False
WGB-TUR09	Front Door for Wall Housing BASIC 09U	535 mm	rauchfarben	391 mm	507 mm	False	False
WGB-TUR12	Front Door for Wall Housing BASIC 12U	535 mm	rauchfarben	523 mm	507 mm	False	False
WGB-TUR15	Front Door for Wall Housing BASIC 15U	535 mm	rauchfarben	658 mm	507 mm	False	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 14-09-2026 . Technical changes reserved.

