



# DATASHEET

## Wall 19" X-Rack Glass door 12U grey RAL7035 3/3



### General data

New generation of 19" wall cabinets, which gives the installer 100% flexibility during installation. The assembly process of the rack is done during the installation of hardware into the cabinet. All the cover elements (side walls, roof + bottom + front door) can be installed on the final end of the job.

Glass front door with steel frame and window of certified safety glass (thickness 4 mm)

Door stop left- or right sided possible

Adjustable door hinges to secure correct leveling of the door.

Protection degree IP20

4 mm<sup>2</sup> Grounding wire and additional electrical connection between steel parts

### Notes:

Quarter turn Lock with key is exchangeable for RUKO/ASSA with compact turning handle Art.-No. 699989.

The Lock is supplied with the cover package for the cabinet (packaging 2 of 3). See e.g. WGX-OxxGR.G

### General Data:

Material & surface front door Steel frame with hardened and tempered glass

Front door hinges Easy pin hinges for left or right side, spring-loaded, adjustable leveling of the door

Degree of protection IP20

This datasheet was created automatically on 04-08-2026 . Technical changes reserved.



# DATASHEET

## Wall 19" X-Rack Glass door 12U grey RAL7035 3/3

Width 600 mm

Height 9U: 500 mm / 12U: 600 mm / 15U: 766 mm

Packaging Package no.3 of 3 : recycled cartonboard

Paint finish RAL7035, light grey / RAL9005, jet black

### Technical properties

|                                    |                                                            |
|------------------------------------|------------------------------------------------------------|
| Cabinet Series                     | 19" Wall Housing X-Rack, un-assembled                      |
| Degree of protection               | IP20                                                       |
| Door opening angle                 | > 180 °                                                    |
| For Cabinet Width                  | 600 mm                                                     |
| Material                           | Glass                                                      |
| Model                              | Stop door                                                  |
| Number of height units (U)         | 9                                                          |
| Profile half-cylinder exchangeable | False                                                      |
| Scope of delivery                  | Tür, inkl. Scharnieren, Handgriff, Erdungskabel, Schlüssel |
| Structure/Use                      | Glastür, einteilig, mit Vorreiberverschluss                |
| Surface finishing                  | Steel elements powder-coated                               |
| Type of closure                    | Single-point latch locking                                 |
| Version as glazed door             | True                                                       |

### Available variants

| ArtNr.        | Bezeichnung                                            | Building width for cabinet build in | Color | Height | Width  | RAL-number | EMC-version | Version as door for disconnecting switch interlocking |
|---------------|--------------------------------------------------------|-------------------------------------|-------|--------|--------|------------|-------------|-------------------------------------------------------|
| WGX-TUR09GR.G | Wall 19" X-Rack<br>Glass door 9U grey<br>RAL7035 3/3   | 600 mm                              | grey  | 500 mm | 600 mm | 7035       | False       | False                                                 |
| WGX-TUR09TS.G | Wall 19" X-Rack<br>Glass door 9U black<br>RAL9005 3/3  | 600 mm                              | black | 500 mm | 600 mm | 9005       | False       | False                                                 |
| WGX-TUR12GR.G | Wall 19" X-Rack<br>Glass door 12U<br>grey RAL7035 3/3  | 600 mm                              | grey  | 600 mm | 600 mm | 7035       | False       | False                                                 |
| WGX-TUR12TS.G | Wall 19" X-Rack<br>Glass door 12U<br>black RAL9005 3/3 | 600 mm                              | black | 600 mm | 600 mm | 9005       | False       | False                                                 |
| WGX-TUR15GR.G | Wall 19" X-Rack<br>Glass door 15U<br>grey RAL7035 3/3  | 600 mm                              | grey  | 766 mm | 600 mm | 7035       | False       | False                                                 |

This datasheet was created automatically on 04-08-2026 . Technical changes reserved.



# DATASHEET

## Wall 19" X-Rack Glass door 12U grey RAL7035 3/3

|               |                                                        |        |       |        |        |      |       |       |
|---------------|--------------------------------------------------------|--------|-------|--------|--------|------|-------|-------|
| WGX-TUR15TS.G | Wall 19" X-Rack<br>Glass door 15U<br>black RAL9005 3/3 | 600 mm | black | 766 mm | 600 mm | 9005 | False | False |
|---------------|--------------------------------------------------------|--------|-------|--------|--------|------|-------|-------|

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-08-2026 . Technical changes reserved.

