DATASHEET

WireXpert MP C6A FQ LAN copper cable-Z. 600Mhz, incl. FO quad modules



General data

The WireXpert MP C6A FQ LAN Copper Cable-Z. 600Mhz from Softing is designed as a CAT 6A certification set for fibre optics and twisted pair. The version includes single-mode fibre and multimode fibre and thus offers a practical solution for certification and measurement tasks.

• CAT 6A fibre and Twisted Pair Certification Kit – Covers fibre and copper applications in one system and supports flexible testing and certification tasks.
• Suitable for network protocol measurement – Extends the range of applications to include protocol measurements, making the set relevant for sophisticated network analysis.
• LCD display, measured value memory and PC/printer interface – ensure a clear representation of the values, facilitate storage and support further processing of the measurement results.

This datasheet was created automatically on 31-10-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

WireXpert MP C6A FQ LAN copper cable-Z. 600Mhz, incl. FO quad modules

In terms of technical design, the solution combines an LCD display with a measured value memory, PC/printer interface and an included measuring head. The power supply is provided by an AC 100-240 V to 12 V; 3 A power supply. This means that the system is designed for use in certification and measurement environments for fibre optics and twisted pairs.

Technical details
- Brand: Softing
- Form: CAT 6A certification set, singlemode fibre, multimode fibre
- Suitable for: fibre Optics, Twisted Pair
- Display type: LCD
- Suitable for network protocol measurement: Yes
- Measured value memory: Yes
- With transducer included: Yes
- With PC/printer interface: Yes
- Power supply: AC 100-240 V to 12 V; 3 A power supply

Technical properties	
Current supply	AC 100-240 V up to 12 V
Dimensions	262 x 120 x 55 mm
Measured value memory	Ja
Net weight	1100 g
Operating Temperature	0 – 40 °C
Storage Temperature	-20 – 60 °C
Suitable for network protocol measurement	Ja
Type of indication	LCD
With PC/printer interface	True

Available variants

ArtNr.	Bezeichnung	Model	Suitable for
WX-MPC6A-FQ	WireXpert MP C6A FQ LAN copper cable-Z. 600Mhz, incl. FO quad modules	Cat-6A certification set;Singlemode Fiber;Multimode Fiber	Fibre optic conductor;Twisted Pair

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION