DATASHEET

WireXpert MP C6A FS LAN copper cable, 600 MHz, incl. FO SM modules



General data

The WireXpert MP C6A FS LAN Copper Cable-Z. 600Mhz from Softing is a CAT 6A certification set with single-mode fibre optics and is suitable for fibre optics as well as twisted pair. The LCD display, the measured value memory and the PC/printer interface support practical measurement and documentation.

• CAT 6A Certification Set with Singlemode fibre – Covers fibre optic and twisted pair testing tasks in one system and supports flexible certification in the network environment.
• Network Protocol Measurement and Measurement Memory – Records measurement results in a structured manner and facilitates traceable evaluation and documentation.
• LCD Display and PC/Printer Interface – Provides clear display of readings and simplifies data output and further processing.

This datasheet was created automatically on 19-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

WireXpert MP C6A FS LAN copper cable, 600 MHz, incl. FO SM modules

In technical use, the WireXpert MP C6A FS LAN connects copper cable-Z. 600Mhz the certification of CAT 6A with functions for fibre optic and twisted-pair environments. The support for network protocol measurement and the existing measured value memory create a reliable basis for test reports. Measurement results can be further processed via the PC/printer interface, while the power supply is provided by an AC 100 240 V to 12 V power supply with 3 A.

Technical details
- Brand: Softing
- Form: CAT 6A certification set, single-mode fibre optics
- Suitable for: fibre Optics, Twisted Pair
- Display type: LCD
- Suitable for network protocol measurement: Yes
- Measured value memory: Yes
- With PC/printer interface: Yes
- Power supply: AC 100-240 V to 12 V; 3 A power supply

Technical properties	
Current supply	AC 100-240 V up to 12 V
Dimensions	263 x 120 x 55 mm
Measured value memory	Ja
Net weight	1100 g
Operating Temperature	0 – 40 °C
Storage Temperature	-20 – 60 °C
Suitable for network protocol measurement	Ja
Type of indication	LCD
With PC/printer interface	True

Available variants

ArtNr.	Bezeichnung	Model	Suitable for
WX-MPC6A-FS	WireXpert MP C6A FS LAN copper cable, 600 MHz, incl. FO SM modules	Cat-6A certification set;Singlemode Fiber	Fibre optic conductor;Twisted Pair

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION