

DATASHEET

WireXpert MP C8 LAN Copper Cable Certifier, Class D to FA, I, II, 3000 MHz



General data

High-End Copper Certifier

The WireXpert MP meets the diverse certification requirements of network environments ranging from small offices and medium-sized companies to large data centers. Its modular design covers all applications from copper (100 kHz to 3000 MHz) and fiber[1] certification (Tier 1, multimode and singlemode).

FEATURES

- The flagship of the WireXpert MP series for copper testing up to Cat 8 and up to 3000 MHz
- Includes 8.2 connectivity, DCRU and TCL[1] measurement, as well as MPTL and EzE test modes
- Fast test times enable users to complete jobs in the shortest possible time
- Fast pre-wiremap to locate wiremap problems even before an autotest is initiated by the user

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.



DATASHEET

WireXpert MP C8 LAN Copper Cable Certifier, Class D to FA ,I, II, 3000 MHz

- With replaceable and cost-effective LONGLIFE test cables

Scope of delivery:

- 2 Mainframe units
- 2 Copper test modules C8
- 2 Cat 8 Channel Test adapters
- 2 Cat 8 Permanent Link test adapters
- 2 LONGLIFE Permanent Link cables
- 2 chargers
- 2 headsets
- 1 Quick Reference Guide
- 1 set of calibration and conformity certificates
- 1 DCRU calibration artifact
- 1 Tri-mode soft case

Technical properties

Current supply	AC 100-240 V up to 12 V
Dimensions	264 x 120 x 55 mm
Measured value memory	Ja
Net weight	1100 g
Operating Temperature	0 - 40 °C
Storage Temperature	-20 - 60 °C
Suitable for network protocol measurement	True
Type of indication	LCD
With PC/printer interface	True

Available variants

ArtNr.	Bezeichnung	Model	Suitable for
WX-MPC8	WireXpert MP C8 LAN Copper Cable Certifier, Class D to FA ,I, II, 3000 MHz	Cat-8 certification set	Twisted Pair

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-10-2026 . Technical changes reserved.

